



# Bowers & Wilkins

## **606 S3**

Technical Information



**Technical features**

Decoupled Double Dome Titanium tweeter  
Continuum™ cone bass / midrange  
Flowport™

**Description**

2-way vented-box system

**Drive units**

1x ø25mm (1 in) Titanium Dome high-frequency  
1x ø165mm (6.5 in) Continuum cone bass / midrange

**Frequency range**

-6dB 40Hz - 33kHz

**Frequency response**

(+/-3dB from reference axis)

52Hz - 28kHz ±3dB

**Sensitivity**

(on axis at 2.83Vrms at 1m)

88dB

**Harmonic distortion**

2nd and 3rd harmonics (90dB, 1m on axis)  
<1% 100Hz - 22kHz  
<0.5% 150Hz - 12kHz

**Nominal impedance**

8Ω (minimum 3.7Ω)

**Recommended amplifier power**

30W - 120W into 8Ω on unclipped programme

**Max. recommended cable impedance**

0.1Ω

**Dimensions**

Height: 344 mm (13.6 in) cabinet only

Width: 189 mm (7.4 in) cabinet only

Depth: 300 mm (11.8 in) cabinet only  
328 mm (12.9 in) including grille and terminals

**Net weight**

7.05kg (15.5lbs)

**Finishes**

Cabinet: Black  
White  
Oak  
Red Cherry (APAC only)

Grille: Black (Black and Red Cherry)  
Grey (White and Oak)