



AVAILABLE AT
DIGITAL CINEMA



Technical features	Decoupled Double Dome aluminium tweeter with Nautilus™ tube loading Kevlar® brand fibre cone bass/midrange Flowport™	
Description	2-way vented-box system	
Drive units	1x ø25mm (1 in) aluminium dome high-frequency 1x ø165mm (6.5 in) woven Kevlar® cone bass / midrange	
Frequency range	-6dB at 45Hz and 50kHz	
Frequency response	52Hz - 22kHz ±3dB on reference axis	
Dispersion	Within 2dB of reference response Horizontal: over 60° arc Vertical: over 10° arc	
Sensitivity	87dB spl (2.83V, 1m)	
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 95Hz - 22kHz <0.5% 140Hz - 20kHz	
Nominal impedance	8Ω (minimum 4.0Ω)	
Crossover frequency	4kHz	
Recommended amplifier power	25W - 100W into 8Ω on unclipped programme	
Max. recommended cable impedance	0.1Ω	
Dimensions	Height:	345mm (13.5 in)
	Width:	190mm (7.5 in)
	Depth:	324mm (12.8 in) cabinet, grille and terminals
Net Weight	6.8kg (14.9 lb)	
Finishes	Cabinet:	Grille:
	Black Ash	Black