



## Studio sound comes home

A substantial, uncompromising three-way floorstander built to fill even the largest rooms with full-blooded, realistic sound. Powerful bass lines come roaring to life, while the speaker's dedicated Continuum™ midrange driver and Carbon Dome™ tweeter lend an astonishing clarity to vocals and treble effects.

## **Technical Specifications**

**Description** 3-way vented-box system

**Technical features** Decoupled Carbon Dome™ tweeter

Continuum™ cone FST™ midrange

Decoupled midrange Aerofoil™ Profile bass cones

Flowport™

**Drive units** 1x ø25mm (1 in) Decoupled Carbon

Dome high-frequency

1x ø150mm (6 in) Continuum cone

FST midrange

2x ø165mm (6.5 in) Aerofoil Profile bass

Frequency range (-6dB) -6dB at 30Hz and 33kHz

Frequency Response -3dB 46Hz - 28kHz ±3dB

**Sensitivity** 89dB spl (2.83V<sub>RMS</sub>, 1m)

**Harmonic distortion** 2nd and 3rd harmonics (90dB, 1m)

<1% 90Hz - 22kHz <0.5% 120Hz - 20kHz

**Nominal impedance**  $8\Omega$  (minimum  $3.1\Omega$ )

Recommended amplifier

power

30W - 200W into  $8\Omega$  on unclipped

programme

**Dimensions** Height: 990mm (39 in) cabinet only

Depth:

1025mm (40.4 in) including plinth

Width: 200mm (7.9 in) cabinet only

320mm (12.6 in) including plinth

300mm (11.8 in) cabinet only

321mm (12.6 in) including grille

and terminals

370mm (14.6 in) including plinth

**Net weight** 25.0kg (55.2 lb)

Finishes Cabinet: Rosenut

Gloss Black Satin White

Grille: Black

Grey (Satin White only)

## Bowers & Wilkins

www.bowers-wilkins.com

Carbon Dome, Continuum, FST, Aerofoil and Flowport are trademarks of B&W Group Ltd.

Copyright © B&W Group Ltd. E&OE