# Bowers & Wilkins



### AVAILABLE AT DIGITAL CINEMA



## Studio sound comes home

A slim, elegant floorstander designed to blend unobtrusively into your home environment, while providing the commanding presence of a much larger speaker. Music is a revelation, with details picked out in pin-sharp detail and with exceptional realism.

#### **Technical Specifications**

-		
Description	3-way vented-box system	
Technical features	Decoupled Carbon Dome <sup>™</sup> tweeter Continuum <sup>™</sup> cone FST <sup>™</sup> midrange Decoupled midrange Aerofoil <sup>™</sup> Profile bass cones Flowport <sup>™</sup>	
Drive units	1x ø25mm (1 in) Decoupled Carbon Dome high-frequency 1x ø130mm (5 in) Continuum cone FST midrange 2x ø130mm (5 in) Aerofoil Profile bass	
Frequency range (-6dB)	-6dB at 43Hz and 33kHz	
Frequency Response -3dB	48Hz - 28kHz ±3dB	
Sensitivity	88dB spl (2.83V <sub>RMS</sub> , 1m)	
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 100Hz - 22kHz <0.5% 300Hz - 20kHz	
Nominal impedance	8Ω (minimum 3.1Ω)	
Recommended amplifier power	30W - 150W into $8\Omega$ on unclipped programme	
Dimensions		
	Height: Width: Depth:	925mm (36.4 in) cabinet only 959mm (37.8 in) including plinth 165mm (6.5 in) cabinet only 252mm (9.9 in) including plinth 255mm (10 in) cabinet only 277mm (10.9 in) including grille and terminals 298mm (11.7 in) including plinth
Net weight	Width:	959mm (37.8 in) including plinth 165mm (6.5 in) cabinet only 252mm (9.9 in) including plinth 255mm (10 in) cabinet only 277mm (10.9 in) including grille and terminals 298mm (11.7 in) including plinth
Net weight Finishes	Width: Depth:	959mm (37.8 in) including plinth 165mm (6.5 in) cabinet only 252mm (9.9 in) including plinth 255mm (10 in) cabinet only 277mm (10.9 in) including grille and terminals 298mm (11.7 in) including plinth

### Bowers & Wilkins

www.bowers-wilkins.com

Carbon Dome, Continuum, FST, Aerofoil and Flowport are trademarks of B&W Group Ltd.

Copyright © B&W Group Ltd. E&OE

This information is intended as a guide only and reflects the current specification at the time of print. We reserve the right to make changes to the specifications