Bowers & Wilkins



AVAILABLE AT DIGITAL CINEMA



Studio sound comes home

Small speaker, big sound. Ideal for smaller rooms, and designed for use on bookshelf or stand, the 707 produces tremendous highs and depths for a compact unit. Its two-way design and advanced drive units make for a sound that's clear, powerful and remarkably cohesive.

Technical Specifications

-		
Description	2-way vented-box system	
Technical features	Decoupled Carbon Dome [™] tweeter Continuum [™] cone bass/midrange Flowport [™]	
Drive units	1x ø25mm (1 in) Decoupled Carbon Dome high-frequency 1x ø130mm (5 in) Continuum cone bass/midrange	
Frequency range (-6dB)	-6dB at 45Hz and 33kHz	
Frequency Response -3dB	50Hz - 28kHz ±3dB	
Sensitivity	84dB spl (2.83V _{RMS} , 1m)	
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 110Hz - 22kHz	
Nominal impedance	8Ω (minimum 4.0Ω)	
Recommended amplifier power	$30W - 100W$ into 8Ω on unclipped programme	
Dimensions	Height: Width: Depth:	280mm (11 in) 165mm (6.5 in) 260mm (10.2 in) cabinet only 276mm (10.9 in) including grille and terminals
Net weight	6.0kg (13.2 lb)	
Finishes	Cabinet:	Rosenut Gloss Black Satin White
	Grille:	Black Grey (Satin White only)

Bowers & Wilkins

www.bowers-wilkins.com

Carbon Dome, Continuum, FST and Flowport are trademarks of B&W Group Ltd.

Copyright © B&W Group Ltd. E&OE