

Bowers & Wilkins

CM Series



# CM Centre 2 S2

CM Centre 2 S2 features a Decoupled Double Dome tweeter, ideal for delivering the clarity needed for dialogue. Below the Decoupled Double Dome tweeter and between the two 6.5-inch bass drivers lies an FST midrange driver. Combined, this makes CM Centre 2 S2 the perfect Home Theatre partner for CM9 S2s.



**AVAILABLE AT  
DIGITAL CINEMA**



Technical features	Nautilus tube loaded Decoupled Double Dome aluminium tweeter Kevlar® brand fibre FST™ midrange Flowport™	
Description	3-way vented-box system	
Drive units	1x ø25mm (1 in) Decoupled Double Dome aluminium high-frequency 1x ø100mm (4 in) Kevlar® cone FST midrange 2x ø165mm (6.5 in) Paper/Kevlar® cone bass	
Frequency range	-6dB at 40Hz and 50kHz	
Frequency response	56Hz - 28kHz ±3dB	
Dispersion	Within 2dB of reference response Horizontal: over 60° arc Vertical: over 20° arc	
Sensitivity	89dB spl (2.83V, 1m)	
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 90Hz - 22kHz <0.5% 120Hz - 20kHz	
Nominal impedance	8Ω (minimum 3Ω)	
Crossover frequency	350Hz, 4kHz	
Recommended amplifier power	30W - 200W into 8Ω on unclipped programme	
Max. recommended cable impedance	0.1Ω	
Dimensions	Height: 225mm (8.9 in) Width: 590mm (23.2 in) Depth: 285mm (11.2 in) cabinet only 301mm (11.9 in) including grille and terminals	
Net weight	18.7kg (41.1 lb)	
Finishes	Cabinet:	Grille:
	Rosenut	Black
	Gloss Black	Black
	Satin White	Grey