



**AVAILABLE AT
DIGITAL CINEMA**



Technical features	Nautilus tube loaded Decoupled Double Dome aluminium tweeter Kevlar® brand fibre cone bass / midrange Flowport™
Description	2-way vented-box system
Drive units	1x ø25mm (1 in) Decoupled Double Dome aluminium high-frequency 1x ø130mm (5 in) woven Kevlar cone bass / midrange
Frequency range	-6dB at 45Hz and 50kHz
Frequency response	50Hz - 28kHz ±3dB
Dispersion	Within 2dB of reference response Horizontal: over 60° arc Vertical: over 10° arc
Sensitivity	84dB spl (2.83V, 1m)
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 110Hz - 22kHz
Nominal impedance	8Ω (minimum 4.0Ω)
Crossover frequency	4kHz
Recommended amplifier power	30W - 100W into 8Ω on unclipped programme
Max. recommended cable impedance	0.1Ω
Dimensions	Height: 280mm (11 in) Width: 165mm (6.5 in) Depth: 260mm (10.2 in) cabinet only 276mm (10.9 in) including grille and terminals
Net weight	6.7kg (14.7 lb)
Finishes	Cabinet: Grille: Rosenut Black Gloss Black Black Satin White Grey