



**AVAILABLE AT
DIGITAL CINEMA**



Technical features Nautilus tube loaded Decoupled Double Dome aluminium tweeter
Kevlar® brand fibre cone FST midrange
Flowport™

Description 3-way vented-box system

Drive units 1x ø25mm (1 in) Decoupled Double Dome aluminium high-frequency
1x ø150mm (6 in) woven Kevlar cone FST midrange
2x ø165mm (6.5 in) paper/Kevlar cone bass

Frequency range -6dB at 30Hz and 50kHz

Frequency response 46Hz - 28kHz ±3dB

Dispersion Within 2dB of reference response
Horizontal: over 60° arc
Vertical: over 10° arc

Sensitivity 89dB spl (2.83V, 1m)

Harmonic distortion 2nd and 3rd harmonics (90dB, 1m)
<1% 90Hz - 22kHz
<0.5% 120Hz - 20kHz

Nominal impedance 8Ω (minimum 3Ω)

Crossover frequency 350Hz, 4kHz

Recommended amplifier power 30W - 200W into 8Ω on unclipped programme

Max. recommended cable impedance 0.1Ω

Dimensions Height: 990mm (39 in) cabinet only
1025mm (40.4 in) including plinth but not feet
Width: 200mm (7.9 in) cabinet only
320mm (12.6 in) including plinth
Depth: 300mm (11.8 in) cabinet only
321mm (12.6 in) inc. grille and terminals
but not plinth
370mm (14.6 in) including plinth

Net weight 26.6kg (58.5 lb)

Finishes Cabinet: Grille:
Rosenuat Black
Gloss Black Black
Satin White Grey