

FPM 2

B&W
Bowers & Wilkins

The FPM2 matches the other models in the FPM Series in terms of timbre and the finish, but the use of a single 4" Kevlar® cone bass/midrange driver allows an ultra-compact design that is ideal for this application.

Like the other models, a Nautilus™ tube-loaded tweeter completes the driver line-up and ensures superb performance, inviting the FPM2 also to be used for 2-channel audio where space is at a premium, especially if combined with a compact subwoofer such as the PV1.

A simple wall bracket is included to mount the speaker flat against the wall. If angling is required, threaded inserts are provided on the back to use an Omnimount® type 10.0 (wall or ceiling) or other compatible bracket.

Alternatively, the speaker will stand freely on a shelf or table when fitted with its detachable rear support leg.

Description: 2-way vented-box system
Frequency Range: -6dB at 65Hz and 40kHz
Frequency Response: 80Hz – 20kHz ±3dB on reference axis
Sensitivity: 86dB spl (2.83V, 1m)
Power Handling: 25W - 100W into 8Ω on unclipped programme

Normal Impedance: 8Ω (minimum 4Ω)
Dispersion: Description: w/in 2dB of reference response
Horizontal: over 40° arc
Vertical: over 10° arc
Dimensions: H 259mm W 170mm D 102mm
H 10.2" W 6.7" D 4"
(including wall plate)
Weight: 2.7 kg / 6 lbs.

B&W Bowers & Wilkins

B&W Group Ltd
Dale Road
Worthing West Sussex
BN11 2BH England

T +44 (0) 1903 221800
F +44 (0) 1903 221801
info@bwgroup.com
www.bwspeakers.com

UK Group (UK Sales)
T +44 1903 221 500
E uksales@bwgroup.com

B&W Group North America
T +1 978 664 2870
E marketing@bwgroupusa.com

B&W Group Asia Ltd
T +852 2 869 9916
E showroom@bwgroup.hk