



**AVAILABLE AT
DIGITAL CINEMA**



Technical features	Decoupled Double Dome aluminium tweeter with Nautilus™ tube loading Kevlar® brand fibre cone FST™ midrange driver Dual-layer aluminium cone bass driver Flowport™	
Description	3-way vented-box system	
Drive units	1x ø25mm (1 in) aluminium dome high-frequency 1x ø100mm (4 in) woven Kevlar® cone FST™ midrange 2x ø165mm (6.5 in) aluminium cone bass	
Frequency range	-6dB at 42Hz and 50 kHz	
Frequency response	50Hz - 22 kHz ±3dB on reference axis	
Dispersion	Within 2dB of reference response Horizontal: over 20° arc Vertical: over 60° arc	
Sensitivity	88dB spl (2.83V, 1m)	
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 95Hz - 22 kHz <0.5% 180Hz - 20 kHz	
Nominal impedance	8Ω (minimum 3.0Ω)	
Crossover frequency	400Hz, 4kHz	
Recommended amplifier power	30W - 150W into 8Ω on unclipped programme	
Max. recommended cable impedance	0.1Ω	
Dimensions	Height:	218mm (8.6 in)
	Width:	590mm (23.2 in)
	Depth:	304mm (12 in) cabinet, grille and terminals
Net Weight	17.2kg (37.8 lb)	
Finishes	Cabinet:	Grille:
	Black Ash	Black