## Bowers & Wilkins



700 Series 2 HTM72 S2





## Studio sound comes home

This high performance two-way centre speaker is a great choice for home cinema set-ups in smaller rooms, where space is at a premium. Partner it up with the more compact 700 Series speakers, such as the 706 or the 704.

Technical Specifications		
Description	2-way vented-box system	
Technical features	Decoupled Carbon Dome <sup>™</sup> tweeter Continuum <sup>™</sup> cone bass/midrange Flowport <sup>™</sup>	
Drive units	1x ø25mm (1 in) Decoupled Carbon Dome high-frequency 2x ø130mm (5 in) Continuum cone bass / midrange	
Frequency range (-6dB)	-6dB at 48Hz and 33kHz	
Frequency Response -3dB	70Hz - 28kHz ±3dB	
Sensitivity	87dB spl (2.83V <sub>RMS</sub> , 1m)	
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 100Hz - 22kHz <0.5% 200Hz - 22kHz	
Nominal impedance	8Ω (minimum 4.3Ω)	
Recommended amplifier power	30W - 120W into $8\Omega$ on unclipped programme	
Dimensions	Height: Width: Depth:	166.5mm (6.6 in) 480mm (18.9 in) 260mm (10.2 in) cabinet only 275mm (10.8 in) including grille and terminals
Net weight	9.11kg (20.1 lb)	
Finishes	Cabinet:	Rosenut Gloss Black Satin White
	Grille:	Black Grey (Satin White only)

## Bowers & Wilkins

www.bowers-wilkins.com

Carbon Dome, Continuum, FST and Flowport are trademarks of B&W Group Ltd.

Copyright © B&W Group Ltd. E&OE