Bowers & Wilkins



Custom Installation ISW-3 and SA250 Mk2



SA250 Mk2 Technical Specifications

Description 250W rack-mount amplifier with built-in

subwoofer equalisation

Amplifier inputs - 2x RCA Phono socket, line in

- 2x RCA Phono socket, link out - 1x XLR socket, line in

- 1x XLR socket, link out

- 3.5mm jack - 12V trigger on/standby (overrides manual standby setting)- 3.5mm jack - 12V trigger equalisation

movie/music

Amplifier outputs - 1x Neutrik® Speakon® 4-pole

speaker socket

- 2x pairs of Binding Posts

Amplifier power output 250WInput impedance $33k\Omega$

Signal / noise >80dB

Rated power consumption 95W – 1/8 full power

30W - Idling

Dimensions Height: 100mm (3.9 in)

[88.5mm (3.5 in) plus feet]

Width: 430mm (16.9 in) Depth: 322mm (12.7 in)

Front panel Height: 2U 88.1mm/3.5 in

Net weight 5.4kg (11.9 lb)

Finish Black

Bowers & Wilkins

www.bowers-wilkins.com

Kevlar is a registered trademark of DuPont. Copyright © B&W Group Ltd. E&OE B&W Group Ltd reserves the right to amend details of the specification without notice in line with technical developments

