AIR SR6



AV/AVIL/AVBLE /AT DIGIT/AVL CINE/AVA

AIR® 6.5" 2-Way Surface Mount Outdoor Speakers

- > High-performance 2-way surface mount loudspeakers
- > Designed for high reliability in both indoor and outdoor applications
- > 6.5" polypropylene woofers for deep, solid bass
- > Optimized dual front ports for enhanced low-frequency response
- > Titanium dome tweeters for crisp, clear high-end extension
- > Rigid ABS plastic construction with powder coated aluminum grilles
- > Versatile and easy-to-install "QuickBall" mounting system
- > Allows 360° rotation and continuously variable positioning
- > 150 Watts program power handling
- > 55Hz-20kHz frequency range
- > 8 Ohms nominal impedance
- > Available in black or white
- > Paintable to blend with surroundings
- > Sold in pairs



AIR® speakers by Crestron® offer superior sound quality and flexible installation in a range of popular sizes for indoor and outdoor applications. Weatherized construction, high power handling, and extended frequency response make AIR speakers an ideal choice for enjoying music out on the deck or around the pool. Their clean, contoured design also makes them a great fit for home theater and other interior applications.

The AIR SR6 model provides a pair of weatherized 2-way surface-mount loudspeakers featuring 6-1/2 inch woofers and 1 inch titanium dome tweeters. Power handling is an impressive 150 Watts (program), with a wide frequency range from 55 Hz to 20 kHz (-10 dB).

AIR SR6 speakers are smartly designed to deliver years of reliable performance and a professional appearance in any residential or small commercial environment. Featuring a unique "QuickBall" mounting system, the AIR SR6 can be mounted to any solid flat surface with the ability to orient and aim the speaker in virtually any position. The QuickBall bracket achieves a very clean and stable installation using a tool-free ball-and-socket mechanism. Simply position the speaker as desired and flip the clamp lever closed. A security screw is included to deter theft by preventing the lever from being released.

The QuickBall mounting bracket can be mounted over a 1-gang US, UK, or European electrical box, allowing wiring to be run through the wall and exit cleanly through the included cover plate. It can also be mounted to a light pole or post using pole-mounting straps (not included). A rear rigging point is also provided for securing the speaker using the optional safety tether kit (SPKA-ST-15^[1]).

Connecting the wire at the back of the speaker is facilitated using a detachable screw terminal block. A weather boot is included to protect the wiring connections from moisture.

AIR speakers are available in white or black, and can be painted to blend with the surrounding architecture. They are priced and sold in pairs.

SPECIFICATIONS

Features & Performance

Woofer: 6.5 inch (165 mm) polypropylene w/rubber surround &

steel basket

Tweeter: 0.98 inch (25 mm) titanium dome

Crossover Frequency: 2 kHz Impedance: 8 Ohms nominal

Frequency Response: 60 Hz to 20 kHz (±3 dB) Frequency Range: 55 Hz to 20 kHz (-10 dB) Power Handling: 150 Watts program

Sensitivity: 88.5 dB @ 1W/1m

Connections

Input: (1) 4-pin 5mm detachable terminal block with screw-down flanges and weather boot;

Speaker input with parallel pass-thru;

Maximum Wire Size: 12 AWG



AIR SR6 AIR® 6.5" 2-Way Surface Mount Outdoor Speakers

Environmental

Temperature: -2° to 120°F (-19° to 49°C) Humidity: 5% to 95% RH (non-condensing)

Construction

Enclosure: ABS plastic, textured finish, paintable **Grille:** Aluminum, powder coated, paintable

Mounting: Surface mount to a solid flat surface with option to position over a flush-mounted 1-gang electrical box, 1-gang UK (BS 4662) electrical box, or 1-gang European (DIN 49073) electrical box; pole mount (straps not included); rigging point for safety tether (SPKA-ST-15 sold separately); theft-resistant security screw

Positioning

Yaw (Horizontal): ±30° Pitch (Vertical): ±30° Roll (Rotation): 360°

Dimensions

Height: 11.19 in (284 mm) Width: 8.08 in (205 mm) Depth: 6.75 in (172 mm);

8.86 in (225 mm) with mounting bracket

Weight

6.6 lb (3.0 kg) per speaker

MODELS & ACCESSORIES

Available Models

AIR SR6-B-T: AIR® 6.5" 2-Way Surface Mount Outdoor Speakers, Black

Textured, Pair

AIR SR6-W-T: AIR® 6.5" 2-Way Surface Mount Outdoor Speakers, White Textured, Pair

Available Accessories

SPKA-ST-15: Safety Tether/Tie Down Kit

Notes:

1. Item(s) sold separately.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron, the Crestron logo, and AIR are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2014 Crestron Electronics, Inc.





Black model – shown with cover removed



QuickBall Mounting Bracket (included)

with cover installed



AIR SR6 - Shown in White



AIR SR6 AIR® 6.5" 2-Way Surface Mount Outdoor Speakers

