

SB 10

Soundbar speaker and subwoofer system

harman/kardon®
by HARMAN



**AVAILABLE AT
DIGITAL CINEMA**

Specifications



■ Harman Kardon® SB 10

A complete 3.1-channel sound system comprised of just two components, the Harman Kardon SB 10 speaker system adds dramatic, high-definition sound to any viewing experience. The sleek central soundbar houses voice-matched left-, right- and centre-channel speakers for outstanding stereo imaging and clean, distinct dialogue, while a 200-watt powered subwoofer delivers the deep, visceral bass so essential to today's most exciting movies.

Choose your AV receiver's virtual surround-sound mode for realistic 3D imaging, or add an additional pair of speakers to build a true 5.1-channel system.

■ Highlights

- Soundbar houses all three front-channel speakers
- Dual-driver centre-channel speaker
- 8-inch (200mm), 200-watt powered subwoofer
- Custom-built drivers work together for optimised performance
- Simple system setup
- Upgradeable to 5.1 channels using HKTS 30SAT surround speakers

■ Features

- Soundbar styled to complement flat-panel TVs
- Soundbar speakers are voice-matched and magnetically shielded
- Subwoofer bass-boost, phase and level controls
- Subwoofer LFE (low-frequency effects) input connection
- Subwoofer auto power on/off
- Soundbar wall-mounting hardware included

SB 10

Soundbar speaker and subwoofer system

harman/kardon
by HARMAN

■ Key Specifications

SB 10 System

- Frequency response: 45Hz – 20kHz (–6dB)

SB 10 Soundbar Speaker

- Low-frequency transducer
 - Left: 76mm (3-inch) paper cone, video-shielded
 - Right: 76mm (3-inch) paper cone, video-shielded
 - Centre: Two 76mm (3-inch) paper cones, video-shielded
- High-frequency transducer
 - Left: 19mm (3/4-inch) silk dome, video-shielded
 - Right: 19mm (3/4-inch) silk dome, video-shielded
 - Centre: 19mm (3/4-inch) silk dome, video-shielded
- Recommended power handling
 - Left and right: 60 watts (each)
 - Centre: 100 watts
- Nominal impedance: 8 ohms (each channel)
- Sensitivity (2.83V/1m): 84dB (each channel)
- Crossover frequency: 2.2kHz, 24dB/octave
- Connector type: push-spring terminals
- Enclosure type: sealed
- Finish: gloss black
- Dimensions (H x W x D): 110mm x 920mm x 89mm (4-5/16" x 36-1/4" x 3-1/2")
- Weight: 3.67kg (8.1lb)

HKTS200SUB Subwoofer

- Low-frequency transducer: 8-inch (200mm) down-firing cone
- Amplifier power: 200 watts
- Frequency response: 45Hz – 200Hz (–6dB)
- Controls: volume, phase, bass boost
- Connections: LFE input; left and right RCA line-level inputs
- Enclosure type: sealed
- Finish: gloss black
- Power requirement: AC 100 – 120V, 50/60Hz, 200W or AC 220 – 240V, 50/60Hz, 200W
- Power consumption: <1W (standby); 200W (maximum)
- Dimensions (H x W x D): 353mm x 267mm x 267mm (13-29/32" x 10-1/2" x 10-1/2")
- Weight: 9kg (19.8lb)

Depth measurement includes knobs, buttons and terminal connections, unless stated otherwise; height measurement includes feet and chassis, unless stated otherwise.