



AVAILABLE AT
DIGITAL CINEMA

beautiful/sound
harman/kardon®
by HARMAN

AVR 370

7.2-channel wireless network-connected audio/video receiver with 125 watts per channel output. Featuring Apple AirPlay, High-Definition Dolby® and DTS® surround-sound decoding, multizone functionality and 4K video scaling.



The AVR cinephiles dream of.

Experience the pinnacle of home entertainment. The Harman Kardon® AVR 370 delivers high-definition video and 125 watts per channel of 7.2-channel surround sound so realistically that the experience of sitting down and watching a movie seems anything but passive. Eight HDMI® inputs, with 3D and Audio Return Channel, including one on the front panel, keep you connected to all your digital components, playing them back in rich, vivid quality. Built-in Wi-Fi® networking and Apple AirPlay software give you wireless access to all the media files on your iPod, smartphone, tablet and computer with remarkable. Elevate your home theater experience to its highest level.



Cinematic experience

- HDMI with 3D, Audio Return Channel, CEC and Deep Colour
- Powerful 7.2-channel surround system
- Dolby® TrueHD and DTS-HD Master Audio™ decoding

Supreme connectivity

- Built-in Wi-Fi networking
- AirPlay-enabled
- 4K video pass-through and scaling
- Control applications for Apple and Android™ products



Made for



SPECIFICATIONS

AVR 370

What's included:

- 1 AVR 370 A/V receiver
- Backlit main remote control with batteries
- Zone II remote with batteries
- Microphone for EzSet/EQ room-correction system
- 1 Detachable IEC power cord
- 1 Quick Start Guide
- 1 AM loop antenna
- 1 FM antenna

Audio Section

- Stereo mode continuous average power: 125 watts/ch, 20Hz – 20kHz, <0.07% THD, both channels driven @ 8 ohms, 6-ohm certified
- Multichannel power: 125 watts/ch, 20Hz – 20kHz, <0.07% THD, two channels driven @ 8 ohms, 6-ohm certified
- Bandwidth @ 1W (+0dB/-3dB): 10Hz – 130kHz
- Input sensitivity/impedance (line-in): 200mV/47k ohms
- Signal-to-noise ratio (IHF-A): 100dB
- Adjacent channel separation
 - Dolby Pro Logic® I/II: 40dB
 - Dolby Digital: 55dB
 - DTS: 55dB

High instantaneous current capability (HCC): ±45 amps
Transient intermodulation distortion (TIM): Unmeasurable
Slew rate: 40V/μsec

FM Tuner Section

- Frequency range: 87.5MHz – 108.0MHz
- Usable sensitivity (IHF): 1.3μV/13.2dBf
- Signal-to-noise ratio (mono/stereo): 70dB/68dB
- Distortion (mono/stereo): 0.2%/0.3%
- Stereo separation: 40dB @ 1kHz
- Selectivity (±400kHz): 70dB
- Image rejection: 80dB
- IF rejection: 90dB

- 125 watts per channel
- Eight HDMI inputs with 3D and Audio Return Channel including one on the front panel, and two HDMI outputs
- 7.2-channel surround sound
- Dolby TrueHD and DTS-HD Master Audio decoding
- Multizone functionality
- Built-in Wi-Fi and AirPlay audio streaming
- DLNA Certified® 1.5 connectivity



AM Tuner Section

- Frequency range: 520kHz – 1,620kHz
- Signal-to-noise ratio: 45dB
- Usable sensitivity (loop): 500μV
- Distortion (1kHz): 50%, mod 0.8%
- Selectivity (±10kHz): 30dB

Video Section

- Television format: PAL, NTSC
- Input level/impedance: 1Vp-p/75 ohms
- Output level/impedance: 1Vp-p/75 ohms
- Video frequency response (composite video): 10Hz – 8MHz (-3dB)
- HDMI: 3D, Audio Return Channel, CEC and Deep Colour

General

- Power requirement: AC 230V/50 – 60Hz
- Power consumption: 120W idle; 1,405W maximum (7 channels driven)
- Dimensions (W x H x D): 440mm x 165mm x 382mm (17-5/16" x 6-1/2" x 15")
- Weight: 8kg (17.6 lb)

- High-definition user interface
- 4K video pass-through and scaling
- Full preamp outputs for use with external power amplifiers
- Complete Zone 2 audio system with remote control
- EzSet/EQ™ technology maximizes sonic performance
- Free downloadable control applications for smartphones and tablets with iOS software and Android application

Let us
entertain
you



With 870 watt of total music power, the S 608 HCS 3 package offers excellent value for money but without compromises in design or sound. Give these speakers a listen and compare them to our competitors' products... we promise you will be surprised!

The S 608 has a 1in tweeter, three 5in midrange drivers ensures strong and clear vocals and instruments while the 10in side-mounted woofer delivers a deep, thunderous bass. The S 608 is fully equipped for optional bi-wiring, and bi-amplification. Furthermore, the easily adjustable spikes ensure that the speakers always stand securely, making a good, stable mechanical contact with the floor.

The centre and satellite speakers come with supplied wall mounts, of course, allowing terrific versatility when it comes to placement options. In closing, we should also mention that all the models in the S 60 series have removable front fabric grilles. You have the choice of leaving them on or off, but, just as importantly, it also shows that we have nothing to hide with these beauties... quite the opposite!

For more information visit www.jamo.com

Specifications	S 608	S 60 SUR	S 60 CEN
System	3 Way Bass reflex	2 Way Bass reflex	2 Way Bass reflex
Woofer (in / mm)	254 / 10	4 / 102	2 x 4 / 102
Midrange	3 x 127 / 5	-	-
Tweeter	1 / 25	1 / 25	1 / 25
Power long/shortterm (W)	150 / 240	80 / 130	80 / 130
Frequency Range (Hz)	37 - 20,000	80 - 20,000	75 - 20,000
Sensitivity (dB/2.8V/1m)	90	87	87
Impedance (Ohm)	6	6	6
Dimensions HxWxD (inches)	44.6 x 7.5 x 13.6	9.4 x 5.2 x 8.3	5.2 x 15.7 x 8.3
Dimensions HxWxD (mm)	1134 x 190 x 380	240 x 133 x 210	133 x 400 x 210

Jamo[®]
Danish Sound Design