

	A 320	A 340	A 3CEN.4	A 3SUB.1	A 3SUB.3	SUB 6510
System	2 Way	2 Way bass reflex	2 Way	Elec. subw.	Elec. subw.	Elec. subw.
Drivers Woofer, Tweeter	3¾/95,1/25 Dome	4/102,1/25 Horn	2 x 3 ¾/95, 1/25	8/203	10/254	10/254
Power (W) long/short term	50/70	70/100	70/100	70/-	100/-	-/650
Frequency Range (Hz)	95-20.000	50 - 20.000	100 – 20.000	45-150	35-150	25-150
Impedance (Ohm)	6	6	8	10 k	22 k	22 k
Dimensions HxWxD/mm	165 x 110 x 91	225 x 160 x 132	113 x 300 x 116	315 x 346 x 345	320 x 390 x 490	375 x 395 x 445
Dimensions HxWxD/inches	6.5 x 4.3 x 3.6	8.9 x 6.3 x 5.2	4.5 x 11.8 x 4.6	12.4 x 13.6 x 13.6	12.6 x 15.4 x 19.3	14.8 x 15.6 x 17.6
Finish	White, Silver, Black	White, Silver, Black	White, Silver, Black	Silver, Black	Black	Black

A 3 Series by Jamo THE UNIVERSAL SOLUTION

www.jamo.com

TECHNOLOGY MADE SIMPLE









A 320PDD.1 (A 320, A 3SUB.1)





A 320PDD.3 (A 320, A 3CEN.4, A 3SUB.3)

THE ENGINEERS' FAVOURITE DETAILS



Two-way system

Despite the small size of the satellite speaker it features a twoway system – a woofer and a tweeter – which reproduces the mid- and upper range frequencies with full fidelity. The result is a very natural sounding vocal quality.

Magnetic shielding

The A 320, A 340 and A 3CEN.4 are all magnetically shielded, making it possible to place the speakers close to a TV without distorting its picture tube.

Electronic overload protection

The electronic PTC resistor limits power to the loudspeaker if it becomes overloaded. When the volume is turned down again, the resistor cools down and the sound is restored to its normal level.

Design

Thanks to their rounded profile, the new A3 speakers can be placed almostanywhere; horizontally or vertically on a bookshelf, on a wall, in a corner – the only limit is your imagination. Due to the ingenious fittings the speakers can be aimed towards the listening position. All accessories for different placement options are included with the speakers.

The new flat design makes the A 3 speakers an even more suitable match for the many new flat screens on the market.

Subwoofer configuration

The concept of offering three different subwoofers, all with variable level and cutoff frequency controls, makes it easy for you to find the perfect solution and to tune the subwoofer to your room and personal preferences.

A 35UB.1 (A 320PDD.1)

A 3SUB.1 is a small cubic designed subwoofer for easy placement in any room. Features a custom designed 8" woofer and a built-in 70 W amplifier

A 3SUB.3 (A 320PDD.3 /A 340PDD.3)

A 3SUB.3 features a custom designed 10" long-throw woofer, a built-in 100 W amplifier, auto On/Off function as well as variable phase control for fine tuning the sound

SUB 6510 (A 340PDD.5)

SUB 6510 features a 10" front firing woofer and is powered by a new amplifier capable of delivering a stunning 650 W peak power! This combined with the closed

cabinet makes this subwoofer deliver a deep and very firm bass, with second to none precision. Other features are auto On/Off function, variable phase control, built-in limiter, and detachable fabric front.







A 340PDD.3 (A 340, A 3CEN.4, A 3SUB.3)

A 340PDD.5 (A 340, A 3CEN.4, SUB 6510)

Accessories

A 320FS/A 340FS - Designed especially for A 320/A 340, and produced in sturdy aluminium to ensure stable placement. The stands feature clever cable management, completely concealing the speaker cables. When mounted on the A 320FS, the A 320 can be adjusted horizontally.

Jamo Audio Grade Silver cable 0.75



