

J R - 4

ROCK SATELLITE



SPECIFICATIONS

FREQUENCY RESPONSE	115Hz-20KHz
DRIVER	4" Long-Throw Aluminum Full-Range Driver
SENSITIVITY	85dB (2.83V @ 1m)
IMPEDENCE	70V / 8 ohm
POWER HANDLING	50W
70V TRANSFORMER	25W
ENCLOSURE MATERIAL	UV Treated Fiberglass
FINISH	Granite, Sandstone
GRILLE MATERIAL	Rust-proof Aluminum
DIMENSIONS	192mm x 226mm x 176mm 7.58" x 8.91" x 6.91"
WEIGHT	2.27 kg (5.0 lbs)
ACCESSORIES (SOLD SEPARATELY)	JDA-500 DSP Amplifier (120V: 10634321, 230V: 10634322)

Jamo

L A N D S C A P E

DESIGN + PERFORMANCE

The satin painted finish and ultra compact design of the JL-4 allows it to blend seamlessly into even the most luxurious of outdoor living spaces, while the 4" long-throw aluminum driver provides detailed, dynamic, balanced sound.

70V / 8 OHM COMPATIBLE

The JR-4 rock satellite is equipped with a high quality 25W 70V transformer - bypassable for 8 ohm operation - for maximum system flexibility for any listening environment, from small residential systems to massive commercial installs.

INTERCHANGEABLE WITH JL-4

The JR-4 utilizes the exact same acoustic components and voicing as the JL-4 landscape satellite, allowing them to be completely interchangeable for great sound in any form factor.

ALL WEATHER DURABILITY

A UV-resistant, fiberglass cabinet provides the utmost in all-weather capability. With an IP45 rating, the Jamo JR-4 rock satellite is lab tested and certified to offer the best in outdoor audio year in and year out.

OPTIMIZED WITH JDA-500

The new Jamo JDA-500 DSP amplifier is the perfect match for the Jamo rock speakers series - with 70V and low impedance compatibility and one-click Jamo speaker presets to optimize the acoustic performance of your Jamo speakers - no amplifier sounds better with Jamo rock speakers.