

J R - 5

ROCK SATELLITE



SPECIFICATIONS

FREQUENCY RESPONSE	93Hz-20KHz
HIGH FREQUENCY DRIVER	1" (2.54cm) Aluminum Tweeter with WaveGuide
LOW FREQUENCY DRIVER	5" (12.7cm) IMG Woofer
SENSITIVITY	88dB (2.83V @ 1m)
POWER HANDLING	60W
70V / 100V TAP SETTINGS	70V: 3.75W, 7.5W, 15W, 30W 100V: 7.5W, 15W, 30W 8 Ohm Bypass
ENCLOSURE MATERIAL	UV Treated Fiberglass
FINISH	Granite, Sandstone
GRILLE MATERIAL	Rust-proof Aluminum
DIMENSIONS (H x W x D)	265mm x 247mm x 234mm 9.46" x 10.35" x 7.97"
WEIGHT	3.62 kg (8 lbs)
ACCESSORIES (SOLD SEPARATELY)	JDA-500 DSP Amplifier (120V: 10634321, 230V: 10634322)

Jamo

L A N D S C A P E

DESIGN + PERFORMANCE

The satin painted finish and ultra compact design of the JR-5 allows it to blend seamlessly into even the most luxurious of outdoor living spaces, while the 1" aluminum tweeter with WaveGuide and 5.25" IMG woofer provide detailed, dynamic, balanced sound.

70V / 100V / 8 OHM MULTI-TAP

The JR-5 rock satellite is equipped with high quality a 30W 70V/100V multitap transformer - with for 8 ohm bypass - for maximum system flexibility for any listening environment, from small residential systems to massive commercial installs.

WAVEGUIDE TECHNOLOGY

Mated to the 1" aluminum tweeter, the WaveGuide focuses high frequency towards the listening area, for more dynamic, detailed sound. The JR-5 features a special 105° design, for extra wide dispersion into the listening space for more balanced, even sound anywhere in the space.

ALL WEATHER DURABILITY

A UV-resistant, fiberglass cabinet provides the utmost in all-weather capability. With an IP45 rating, the Jamo JR-5 rock satellite is lab tested and certified to offer the best in outdoor audio year in and year out.

OPTIMIZED WITH JDA-500

The new Jamo JDA-500 DSP amplifier is the perfect match for the Jamo rock speakers series - with 70V and low impedance compatibility and one-click Jamo speaker presets to optimize the acoustic performance of your Jamo speakers - no amplifier sounds better with Jamo rock speakers.