

J R - 8 S W

ROCK SUBWOOFER SPEAKER

Jamo

L A N D S C A P E



DESIGN + PERFORMANCE

The satin painted finish and compact design of the JR-8SW allows it to blend seamlessly into even the most luxurious of outdoor living spaces, while the 8" dual voice coil IMG woofer provides powerful, dynamic, balanced low frequencies for any outdoor audio system.

TRANSFORMERLESS 70V/100V

The JR-8SW rock subwoofer is equipped with a powerful dual voice coil woofer, allowing for completely transformerless 70V or 100V operation, for seamless integration into distributed audio systems without the low frequency degradation of a transformer. 16 ohm or 4 ohm mono, or 2 x 8 ohm stereo is also possible, for maximum system flexibility in any listening environment, from small residential systems to massive commercial installs.

ALL WEATHER DURABILITY

A UV-resistant, fiberglass cabinet provides the utmost in all-weather capability. With an IP45 rating, the Jamo JR-8SW rock subwoofer is lab tested and certified to offer the best in outdoor audio year in and year out.

OPTIMIZED WITH JDA-500

The new Jamo JDA-500 DSP amplifier is the perfect match for the Jamo rock speakers series - with 70V and low impedance compatibility and one-click Jamo speaker presets to optimize the acoustic performance of your Jamo speakers - no amplifier sounds better with Jamo rock speakers.

SPECIFICATIONS

FREQUENCY RESPONSE	38Hz-125Hz
DRIVER	8" (20.3cm) DVC IMG Woofer
SENSITIVITY	87dB (2.83V @ 1m)
POWER HANDLING	2 x 50W
IMPEDANCE	2 x 8 Ohm / 70V / 100V
ENCLOSURE MATERIAL	UV Treated Fiberglass
FINISH	Granite, Sandstone
GRILLE MATERIAL	Rust-proof Aluminum
DIMENSIONS (H x W x D)	327mm x 379mm x 288mm 12.87" x 14.92" W x 11.35"
WEIGHT	6.12 kg (13.5 lbs)
ACCESSORIES (SOLD SEPARATELY)	JDA-500 DSP Amplifier (120V: 10634321, 230V: 10634322)