

# PRO-6504-L-THX



## THX® SELECT2 CERTIFIED

Delivers effortless dynamic range and brings superior sound to larger areas thanks to its highly regarded THX Select2 certification. It not only delivers consistent compelling audio to larger-sized rooms it also brings real cinema sound to the comforts of home without taking up any floor space.

## CINEMA QUALITY SOUND

Employs high output fiberglass woofers for powerful bass impact, while a 1-inch titanium tweeter mated to a new symmetrical pattern 90 x 90 square Tractrix® Horn generates flat in-room frequency response with high efficiency and low distortion.

## MAXIMUM INSTALLATION RELIABILITY

This in-wall speaker also consistently delivers thrilling, realistic sound, whether it's installed horizontally or vertically. It features sure-grip mounting dogs that provide even pressure against drywall for long-term installation reliability, and includes a paintable grille that blends in perfectly with any décor.

## UNLIMITED FLEXIBILITY

Timbre matched to all of our THX-certified products, so you can mix and match to create an unbeatable, discreet stereo or home theater system that's just right for you.

## EDGE-TO-EDGE GRILL

Covering the whole of the speaker makes painting the product both simpler and quicker. Premium Neodymium magnets make it easy to install and remove and ensure a secure and flush fit without any moving parts. The flat grill allows better harmonization with today's modern interior designs and disappear into the background, enabling sound to take center stage.

## SEAMLESS HIGH PERFORMANCE

The Klipsch Professional Series introduces a new line of high-performance architectural speakers unlike any you've heard before. Superior acoustic technology makes the Professional Series the most dynamic, powerful, direct-radiating speakers available.

## SPECIFICATIONS

SYSTEM	2-way In-wall
FREQUENCY RESPONSE	46 Hz - 20 kHz +/- 3dB
POWER HANDLING (Cont/Peak)	150W/600W
RECOMMENDED AMP POWER	150W
SENSITIVITY	92 dB
IMPEDANCE	8 Ohms compatible
HIGH FREQUENCY DRIVER	1" (2.5cm) Titanium diaphragm compression driver mated to 90° x 90° square Tractrix® Horn
HIGH FREQUENCY Crossover	250 Hz & 2100 Hz
LOW FREQUENCY DRIVER	Four 5.25" (13.3cm) high-output, fiberglass cone woofers
ENCLOSURE MATERIAL	MDF & Aluminum motorboard /ABS frame
ENCLOSURE TYPE	Infinite baffle, front flush with wall
HOLE DIMENSION	27.25" (69.2cm) H x 6.5" (16.5cm) W
DIMENSIONS	28.5" (72.4cm) H x 8" (20.3cm) W
MOUNTING DEPTH	3.75" (9.5cm)
WEIGHT	18.3lbs (8.3kg)
FINISH	White paintable grill