R-40SA



AVAILABLE AT DIGITAL CINEMA



TAKE YOUR MOVIES AND MUSIC TO NEW HEIGHTS

Immersive sound comes alive from all directions (including overhead!) with these Dolby Atmos® enabled speakers. Add them to any monitor or tower speaker or use as surround speakers for a hemisphere of rich, detailed sound.

ALL NEW 90° X 90° TRACTRIX HORN

Our exclusive Tractrix® horn technology delivers the power, detail and emotion of the live music experience with the cleanest, most natural sound possible. The increased outer horn dimensions allow for directivity control over a larger bandwidth of frequencies, resulting in improved high frequency directivity and a more accurate sound stage.

LINEAR TRAVEL SUSPENSION (LTS) ALUMINUM TWEETER WITH KAPTON SUSPENSION

The exclusive Linear Travel Suspension (LTS) minimizes distortion for enhanced, detailed performances. Aluminum is an extremely light and rigid material used in the tweeter assembly to provide high efficiency and improve resolution and detail. LTS tweeters are a hallmark of Klipsch speakers, making it a core component of some of the best speakers in the world.

SPUN-COPPER THERMOFORMED CRYSTALLINE POLYMER (TCP) WOOFERS

Utilizing trickle-down technology from Klipsch's highly acclaimed Reference Premiere series, the TCP woofers have steeper angling of the cones for a smoother response and improved accuracy and transparency. The additional ribbing increases the overall rigidity for less cone breakup at higher frequencies.

SLEEK, MODERN APPEARANCE

Hidden fasteners, edge-to-edge horn, and low-profile magnetic grilles give the speakers a polished, modern appearance.

MDF CABINET WITH SCRATCH-RESISTANT, TEXTURED WOOD GRAIN VINYL

Stylish aesthetic with absolute durability that results in a seamless integration into any décor.

HIGH QUALITY CABINET DESIGN

Reinforced 3/4" MDF construction with an all-new bracing design reduces cabinet vibration for less audible coloration and improved sonic accuracy.

CABLES INCLUDED

Jumper wires are included in the box for an easy Dolby Atmos connection to the R-800F and R-600F floorstanding speakers.

SPECIFICATIONS

Conforms to Dolby Atmos Specifications
Conforms to Dolby Atmos Specifications
50W/100W
8 ohms Compatible
4,400 Hz
1" Aluminum LTS tweeter mated to a 90 x 90 square Tractrix® Horn
4" spun-copper TCP woofer
MDF
Acoustic Suspension
Single Gold Plated Binding Posts
7" (178 mm)
5.75" (146 mm)
12.7" (298 mm)
6 lbs (2.8 kg)
Black Textured Wood Grain Vinyl
Rubber Feet (4)

*SPL at 1M, half-space anechoic with 2.83V input

3502 WOODVIEW TRACE INDIANAPOLIS, IN 46268 | KLIPSCH.COM

All specifications are subject to change without notice. @2021 Klipsch Group, Inc. Klipsch and Tractrix are registered trademarks of Klipsch Group, Inc. A wholly-owned subsidiary of Voxx International Corporation.