# **RP-504C**







SPECIFICATIONS	
FREQUENCY RESPONSE	58-25kHz +/- 3dB
SENSITIVITY	97dB @ 2.83V / 1m
POWER HANDLING (CONT/PEAK)	150W/600W
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	500Hz/1500Hz
HIGH FREQUENCY DRIVER	1" Titanium LTS Vented Tweeter with Hybrid Cross-Section Tractrix® Horn
LOW FREQUENCY DRIVER	Quad 5.25" Cerametallic Cone Woofers
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass Reflex via rear-firing Tractrix® Port
INPUTS	Single Binding Posts
HEIGHT	6.81" (17.3 cm)
WIDTH	31.13" (79.1 cm)
DEPTH	14.46 (36.7 cm)
WEIGHT	34 lb (15.4 kg)
FINISH	Ebony, Walnut, Piano Black
ACCESSORIES	Rubber Feet (4)
BUILT FROM	2018

### 90° x 90° SILICON COMPOSITE HYBRID TRACTRIX® HORN

Horn loading maximizes efficiently and increases detail while focusing high frequencies towards the listening area. Proprietary Tractrix® geometry provides the most efficient transfer of high frequency waves into the listening area. The phase plug and compressed molded silicon face ensure smooth frequency response. When combined, the cleanest, most natural sound possible is created.

## LINEAR TRAVEL SUSPENSION (LTS) TITANIUM DIAPHRAGM TWEETER

The exclusive Linear Travel Suspension minimizes distortion for enhanced, detailed performance. LTS tweeters are a hallmark of previous Reference lines, making it a core component of some of the best speakers in the world.

#### **VENTED TWEETER DESIGN**

The new vented tweeter housing reduces standing waves that create unwanted harmonics, resulting in enhanced detail and clarity in high frequency reproduction.

#### SPUN COPPER CERAMETALLIC WOOFERS

A signature feature on the Reference Premiere series, Cerametallic™ woofers are exceptionally rigid and lightweight for minimal distortion and maximum efficiency. When paired with the Tractrix horn-loaded LTS tweeter, it provides the highest speaker efficiency in its class.

#### TRACTRIX PORTS

Utilizing Tractrix geometry, the Reference Premiere ports allow for the most efficient, fastest air transfer from the cabinet, which reduces port noise for punchier low frequencies. Klipsch Tractrix ports have custom designed inner flares that help reduce air turbulence entering the port. Less turbulent air helps reduce port noise for cleaner, more powerful bass.

### **ROBUST INPUT TERMINALS**

Single 5-way screw terminals accept banana plugs or bare wire up to 12-gauge for flexible, lasting connections while the vibrant color coding provides easy set-up and connection.

#### **FURNITURE GRADE MATERIALS AND FINISHES**

Finishes include ebony vinyl, walnut vinyl and piano gloss. Ebony and walnut models boast satin painted baffles with a scratch resistant finish, while the premium piano gloss cabinet is hand-sanded for a clear, mirror-like finish. The mirror-life piano gloss finish is seamless due to the meticulous hand sanded and hand polished process.

## STRONG, FLEXIBLE, REMOVABLE GRILLE

Attaches magnetically for an elegant transition from powerful showstopper to discrete performance piece.

#### **DRAMATIC DETAILS**

Copper anodized trim rings, cast aluminum feet, satin painted baffles and a laser etched logo treatment give the Reference Premiere II series a modern, premium look.