

THX-6000-LCR(L/R)

Dual 6.5" Two-Way THX® Ultra2™
Certified LCR Loudspeaker

**DIGITAL
CINEMA**

**AVAILABLE AT
DIGITAL CINEMA**



THX-6000-LCR (L)



THX-6000-LCR (R)

THE THX-6000-LCR IS A THX® ULTRA2 CERTIFIED LOUDSPEAKER.

It was designed primarily for front left-, center-, and right-channel reproduction in large, ultimate-performance home theaters. It can also be used for surround channels, however, and is equally suitable for combination home-theater/music systems demanding superb sound and high output capability. Its enclosure is front-ported to facilitate installation in custom cabinetry and has back - panel 1/4" - 20 threaded inserts compatible with the Klipsch SB-9 mounting bracket or any high quality wall/ceiling speaker mount rated for 40lbs or higher load.

THE THX-6000-LCR DESIGN EMERGES DIRECTLY FROM KLIPSCH'S EXPERIENCE AS A LEADING SUPPLIER OF CINEMA SOUND SYSTEMS.

A large, rectangular 90° x 60° Tractrix® Horn raises the efficiency of the speaker's 1-inch titanium-dome compression driver tweeter and optimizes its radiation pattern. The horn enables the speaker to meet THX Ultra2 directivity specifications without the lobing and comb filtering effects that afflict conventional multiple-tweeter solutions. And its dual 6.5" woofers have large, magnetically shielded motor structures that drive rigid, low-mass Cerametallic™ anodized-aluminum cones for high output and low distortion.

CONSTRUCTION IS TO THE HIGHEST STANDARD.

With a professional grade rabbet and dado locked panel cabinet and premium components throughout to ensure sonic purity, consistency, and reliability.



SPECIFICATIONS

FREQUENCY RESPONSE	48Hz - 20kHz ± 3dB
SENSITIVITY	97dB @ 2.83 volts / 1 Meter
NOMINAL IMPEDANCE	8 ohms compatible
HF CROSSOVER	1400Hz
POWER HANDLING	150 watts maximum continuous (600 watts peak)
ENCLOSURE TYPE	Bass Reflex via front-mounted port
ENCLOSURE MATERIAL	Medium density fibreboard construction (MDF)
TWEETER	1" (2.5cm) magnetically shielded, titanium dome compression driver with 9.6oz ceramic magnet structure.
HIGH FREQUENCY HORN	10" x 6" rectangular 90° x 60° Tractrix® Horn
WOOFER	Two 6.5" (16.5cm) magnetically shielded, Cerametallic™ cone, cast aluminium frame drivers
INPUT CONNECTIONS	Two sets of binding post speaker terminals (connected via brass strap jumpers)
DIMENSIONS	15" (38.1cm) H x 17" (43.2cm) W x 12.5" (31.8cm) D (w/grille)
WEIGHT	39 lbs. (17.7kg)
FINISH	Galaxy Black cabinet with Black anodized aluminum fascia
MOUNTING	4-Bolt pattern 1/4" - 20 thread

Klipsch®
KEEPERS OF THE SOUND

3502 WOODVIEW TRACE INDIANAPOLIS, IN 46268 | KLIPSCH.COM/CUSTOM

All specifications are subject to change without notice. ©2019 Klipsch Group, Inc. Klipsch, Keepers of the Sound and Tractrix are registered trademarks of Klipsch Group, Inc. a wholly-owned subsidiary of Voxix International Corporation.