

THX-8000-L



THX® ULTRA CERTIFIED

Works well with multi-channel movie and music presentations playing up to reference levels in rooms of 3,000 cubic feet or larger.

CINEMA QUALITY SOUND

Employs high output aluminum woofers for powerful bass impact, while a 1-inch titanium tweeter mated to symmetrical pattern 80 x 80 Tractrix® Horn generates flat in-room frequency response with high efficiency and low distortion.

MAXIMUM INSTALLATION RELIABILITY

This in-wall speaker also consistently delivers thrilling, realistic sound, whether it's installed horizontally or vertically. It features sure-grip mounting dogs that provide even pressure against drywall for long-term installation reliability, and includes a paintable grille that blends in perfectly with any décor.

UNLIMITED FLEXIBILITY

Timbre matched to all of our THX-certified products, so you can mix and match to create an unbeatable, discreet stereo or home theater system that's just right for you.

EDGE-TO-EDGE GRILL

Covering the whole of the speaker makes painting the product both simpler and quicker. Premium Neodymium magnets make it easy to install and remove and ensure a secure and flush fit without any moving parts. The flat grill allows better harmonization with today's modern interior designs and disappear into the background, enabling sound to take center stage.

SPECIFICATIONS	
SYSTEM	2-way In-wall
FREQUENCY RESPONSE	80Hz-20kHz +/- 3dB
POWER HANDLING (Cont/Peak)	150W/600W
SENSITIVITY	91dB
IMPEDANCE	8 Ohms
CROSSOVER FREQUENCY	2300Hz
HIGH FREQUENCY DRIVER	1" (2.5cm) Titanium dome compression driver mated to 80° x 80° Tractrix® Horn
LOW FREQUENCY DRIVER	8" (20cm) Aluminum Cone Woofer
ENCLOSURE TYPE	Sealed Enclosure
HOLE DIMENSION	19" (48.3cm) H x 10" (25.4cm) W
DIMENSIONS	20.8" (52.7cm) H x 11.8" (29.8cm) W
MOUNTING DEPTH	3.7" (9.4cm)
WEIGHT	17.5 lbs. (7.9kg)
FINISH	White paintable grill