# marantz®



### HD-DAC1 HEADPHONE AMPLIFIER WITH DAC-MODE



The HD-DAC1 is so powerful, it can even drive audiophile high-impedance headphones of up to 600 ohm - with complete MODE ease. All thanks to its three-level gain control, Marantz HDAM-SA2 modules, a high current audiophile DAC (CS4398), and its Premium Quality fixed and variable RCA outputs. It is so powerful, it not only drives headphones, you can also directly connect it to your Hi-Fi integrated amplifier or to a pair of active speakers or power amps. It's also highly connectable. Optical and coaxial digital inputs as well as a USB-B port enable you to stream music directly from your PC or MAC. iDevices can also be connected via the USB port on the front. For even more connectivity we have also included an analogue input. The USB-B works in asynchronous mode to support not only 192 kHz / 24bits high-resolution audio but also the DSD 2.8MHz and 5.6MHz for maximized performance and the most direct way to enjoy excellent quality. To safeguard quality when connected to a computer, we built extended isolation around the USB-B input to eliminate the chance of high frequency noise generated by the computer entering the HD-DAC1. We even included a jitter remover and Dual Clock for extreme accuracy. Without doubt, the HD-DAC1 is a feast for the ears. It also looks good. Info on volume, input, resolution, etc. is shown on the stylish Marantz Porthole Display. While the solid aluminum front is supported by a double layer bottom plate and retro-style side panels. Pure craftsmanship.





### **Main Features**

- High quality Headphone amplifier with DAC Mode
- 2x optical, coaxial and USB type B digital inputs capable of 192kHz/24bit
- Native DSD2.8 and 5.6 support
- Asynchronous mode
- High quality D/A converter CS4398
- Jitter remover
- Dual Clock
- Noise isolation for all digital inputs (USB-A, Optical, Coaxial, USB-B)
- HDAM & HDAM-SA2
- Gain control to support wide range of headphones
- Fix and variable RCA output
- iDevice capable front USB input
- Gold plated fix level and variable level RCA output terminals
- Available in black & silvergold

#### EAN

EU	HDDAC1/N1B	4951035054369	Black
	HDDAC1/N1SG	4951035054352	Silvergold
UK	HDDAC1/T1B	4951035054369	Black
	HDDAC1/T1SG	4951035054352	Silvergold

www.marantz.eu

because music matters



## HD-DAC1 HEADPHONE AMPLIFIER WITH DAC-MODE



DAC operation mode: USB / Coax / Optical       • / • / •         Asynchronous mode rear USB       •         Bit-perfect transmission       •         USB-B DSD Audio Streaming: DSD2.8 / DSD5.6       • / •         Ground isolator for DAC Mode operation       •         iPod / iPhone compatible USB input       •         DAC chip       CS4398         Jitter reducer       •         HDAM version       HDAM+HDAM SA2	
Bit-perfect transmission       •         USB-B DSD Audio Streaming: DSD2.8 / DSD5.6       • / •         Ground isolator for DAC Mode operation       •         iPod / iPhone compatible USB input       •         DAC chip       CS4398         Jitter reducer       •	
USB-B DSD Audio Streaming: DSD2.8 / DSD5.6       • / •         Ground isolator for DAC Mode operation       •         iPod / iPhone compatible USB input       •         DAC chip       CS4398         Jitter reducer       •	
Ground isolator for DAC Mode operation       •         iPod / iPhone compatible USB input       •         DAC chip       CS4398         Jitter reducer       •	
iPod / iPhone compatible USB input     •       DAC chip     CS4398       Jitter reducer     •	
DAC chip CS4398 Jitter reducer •	
Jitter reducer  •	
HDAM version HDAM+HDAM SA2	
High Grade Audio Components	
Customised Components	
INPUTS/OUTPUTS	
Headphone Out	
Headphone Volume Control	
Headphone Gain Control (low / mid / high) •	
Analogue Input 1	
Analogue Out (fix / variable) • / •	
Digital Optical In / Out 2 / -	
Digital Coaxial In / Out 1 / -	
Sample Rate digital In 192kHz/24bit	
Gold plated Cinch	
Front USB •	
USB type B input for Computer (back) •	
Asynchronous mode rear USB •	
Sample Rate USB type B In 192kHz/24bit	
USB-B DSD Audio Streaming: DSD2.8 / DSD5.6 •	
D-Bus •	

SPECIFICATIONS	
Frequency Response	2 Hz - 20 kHz
Signal to Noise Ratio	106 dB
Total Harmonic Distortion	0,0012%
Channel Separation	100 dB
Headphone Power	800mW / 32 ohm
GENERAL	
Available colors: Gold / Silver / Black / Silver-Gold	-/- / • / •
Available colors: Gold / Silver / Black / Silver-Gold Remote Control	-/- / • / • RC001HD
Remote Control	RC001HD
Remote Control Standby Consumption in W	RC001HD 0.3
Remote Control Standby Consumption in W Auto power off	RC001HD 0.3
Remote Control Standby Consumption in W Auto power off Detachable Power Cable	RC001HD 0.3 •

Design and specifications are subject to change by Marantz without notice.