

CM


CEILING MOUNT

Designer Aesthetics
Audiophile Performance
Installation Ease

PERFORMANCE LOUDSPEAKER SPECIFICATIONS SHEET

DIGITAL
CINEMA

AVAILABLE AT
DIGITAL CINEMA



CM8PR

8" 2-WAY LEFT/CENTER/RIGHT
CEILING-MOUNT LOUDSPEAKER



Performance loudspeakers are optimal for primary and secondary listening rooms and home theater applications. Glass fiber woofer cones and proprietary Teteron® tweeters extend the frequency response for a superior listening experience.

FEATURES AND BENEFITS

- **Designer Aesthetics** Magnetically attached MicroThin™ speaker grilles ensure a clean, virtually invisible appearance that blends with the room's aesthetics. Optional square grilles provide added design flexibility.
- **Superior Sound Quality** Precision tuned and voiced fixed woofer ceiling-mount loudspeakers provide graduated performance for all types of applications. Whether you are listening to background talk radio or a complete orchestra, Niles CM series delivers optimal performance and reliability.
- **Installation Ease** Three patent-pending spring tensioned mounting clamps permit quick installation and compensate for uneven mounting surfaces and varied environmental conditions. Weather-resistant construction enables installation in moist areas, such as bathrooms or outdoors under eaves.
- **Install With Confidence** The best-built loudspeakers deserve the best protection—the Niles Lifetime Limited Warranty.

2-WAY CEILING-MOUNT LOUDSPEAKERS

CM8PR

8" 2-Way Left/Center/Right Ceiling-Mount Loudspeaker



For advanced home theaters and primary listening rooms



Packaged Individually with Round MicroThin™ Grille

Stock Number

FG01662

RELATED PRODUCTS	
	SG8C 8" Square Loudspeaker Grille Stock Number: FG01646
	NCB8C 8" New Construction Bracket Stock Number: FG01648

FEATURES

- Integrated woofer/baffle design delivers greater low frequency response by employing an 8" woofer where competitive models of the same outer size use smaller woofers.
- Glass fiber woofer cone is extremely rigid to reduce breakup, lower distortion and provide enhanced bass response
- Butyl rubber surround damps resonance and provides exceptional durability
- 1" fluid-cooled Teteron® dome tweeter offers enhanced dispersion and silky-smooth high frequency response
- Proprietary bridge-mounted tweeter pivot mechanism focuses the high frequency sound in any direction up to 20° without diffraction
- Magnetically attached, rust-resistant grille covers install quickly and provide a low profile look
- Weather resistant construction reduces installation limitations and provides unique solutions in moist environments like bathrooms or outdoors under eaves
- Patent-pending spring tensioned mounting clamps permit quick installation and compensate for uneven mounting surfaces and varied environmental conditions

SPECIFICATIONS

- Frequency response: 48Hz to 21kHz +/-3dB
- Impedance: 8 ohm nominal; 6 ohm minimum
- Recommended amplifier power: 10 to 140 watts

DIMENSIONS


- Frame Dimensions: 11 3/8 inches (28.9 cm)
- Hole cutout dimensions: 9 3/4 inches (24.8 cm)
- Depth behind ceiling (5/8" drywall): 4 1/8" (10.5 cm)
- Shipping Weight: 6.4 lbs (2.9 kg)

WARRANTY: Lifetime Limited



NILES®

BLENDING HIGH FIDELITY AND ARCHITECTURE®



CM4PR
3.5" Performance

CM7BG
7" Background

CM7SD
7" Shallow Depth

CM7MP
7" Multi Purpose

CM7PR
7" Performance

CM7HD
7" High Definition

CM7FX
7" Surround Effects

CM7SI
7" Stereo Input

CM8MP
8" Multi Purpose

CM8PR
8" Performance

CM8HD
8" High Definition

CM8SI
8" Stereo Input

1-800-BUY-HIFI – www.nilesaudio.com

©2011 The AVC Group, LLC. All Rights Reserved. Niles, the Niles logo and Blending High Fidelity and Architecture are registered trademarks of The AVC Group, LLC. MicroThin is a trademark of The AVC Group, LLC. All other trademarks are the property of their respective owners. We reserve the right to change features, descriptions, and/or specifications at any time without notice. CS0326A