

# ALPHA PS1

POWERED SPEAKERS FOR ALL YOUR MEDIA

**psb**  
SPEAKERS

DIGITAL  
CINEMA

AVAILABLE AT  
DIGITAL CINEMA



## SPECIFICATIONS

### FREQUENCY RESPONSE

On Axis @ 0° ± 3dB	80-22,000Hz
On Axis @ 0° ± 1 1/2dB	90-20,000Hz
Off Axis @ 30° ± 3dB	90-12,000Hz
LF Cutoff -10dB	58Hz

### AMPLIFIER POWER

Continuous	2 x 20W
Dynamic Peak	2 x 40W
Type	Class D

### ACOUSTIC DESIGN

Tweeter (Nominal)	3/4" (19mm) Aluminium Dome
Woofer (Nominal)	3 1/2" (90mm) Polypropylene Cone Rubber Surround
Crossover	2100Hz LR4
Internal Volume	.067 ft <sup>3</sup> (1.9 litre)
Design Type	Bass Reflex Rear Slot Port

### SIZE (W x H x D)

Gross Dimensions including Feet and Terminals	4 1/2 x 7 7/8 x 6 7/8" * (114 x 197 x 174mm)
---	---

### WEIGHT

Net	8.3lb (3.8kg)/pr
Shipping	12lb (5.5kg)/pr

### FINISH

Gloss Black

### FEATURES

Volume Control  
Mono Subwoofer Output  
Low Level RCA Input  
Low Level 1/8" (3mm) "AUX" Input

### ACCESSORIES

Power Supply Brick  
Power Link  
White Drawstring Bag

\*Non-metric measurements are approximate.

All specifications are subject to change without notice. PSB, PSB Speakers, and Alpha are trademarks of, or used under license by, PSB Speakers, a division of Lenbrook Industries Limited.  
© 2013 PSB Speakers 12-026. All rights reserved. Printed in October 2013.

REAL SOUND for REAL PEOPLE