

# M4U 2 Active Noise Cancelling Headphones

**psb**  
SPEAKERS



**AVAILABLE AT  
DIGITAL CINEMA**



## SPECIFICATIONS

FREQUENCY RANGE		
-10dB		10Hz
-3dB		15Hz
±1 1/2dB		20-20,000Hz
SENSITIVITY		
1kHz/1mW		102dB
THD, Total Harmonic Distortion		
ANC: ON (1kHz/1mW)		0.5%
ANC: OFF (1kHz/1mW)		0.25%
POWER HANDLING		
Maximum		30mW
IMPEDANCE		
Passive		32 Ohms
Active/ANC		10k Ohms
BATTERY LIFE		
Active Noise Cancelling ON		60 hours
TRANSDUCER		
Type		Dynamic
Operating Principle		Closed
Size		40mm
EAR COUPLING		
		Circumaural
CONNECTION		
		3.5mm (1/8") Stereo Jack (Left or Right)
CABLES		
Push Function & Monitor Cable	Length Type	1.5m (59") Detachable Tangle-free
Monitor Cable	Length Type	1.5m (59") Detachable Tangle-free
CONSTRUCTION		
Headband		Polycarbonate
Driver Enclosure		ABS+Polycarbonate
Earpads and Headpad Covering		Leatherette
Travel Case		EVA
SIZE (W x H x D)		
Overall		7 7/8 x 7 7/8 x 2 7/8" (200 x 200 x 70mm)
Ear Cushion Outside		2 3/4 x 3 7/8 x 3/4" (68 x 98 x 17mm)
FINISH		
		Gloss Black
FEATURES		
		Tri-mode—Active Mode with Noise Cancelling, Active Mode, and Passive Mode (without Batteries) Dual Input Connection (Left or Right) Efficient Active Electronics for Long Battery Life Comfort Fit Gyro-suspended Replaceable Ear Pads Easy Folding for Travel and Storage Convenient Remote and Stereo Monitor Controls with Mic for iPhone and BlackBerry
ACCESSORIES INCLUDED		
		Protective Travel Case Extra Ear Pads 2 x 1.5m cables 1/8" to 1/4" (3.5mm to 6.3mm) Stereo Plug Adaptor Airline Connection Adaptor 2 x AAA Batteries Cleaning Cloth

All specifications are subject to change without notice. PSB and PSB Speakers are trademarks of, or used under license by, PSB Speakers, a division of Lenbrook Industries Limited.  
© 03/12 PSB Speakers. 11-066 All rights reserved.

REAL SOUND for REAL PEOPLE