

# A-30-K

Direct Energy Design Integrated Amplifier with Symmetrical Construction, Aluminium Rotary Knob and Panels, and Phono MM



REAR PANEL



A-30-K/PWSYXE8

## DESIGN & BUILD

- › Direct Energy Design Amp
- › Symmetrical Power Amp
- › Clean Ground Construction
- › Isolated Power Supply
- › Source Direct Mode
- › Power Amp Direct Mode
- › Trans-Stabilizer
- › Speaker A, B, A+B Selector
- › Aluminium Rotary Knob
- › Aluminium Panels
- › Auto Power Down

## CONNECTIONS

- › Analogue Audio Input (PHONO (MM), TUNER, SACD/CD, AUX, NETWORK, RECORDER, POWER AMP DIRECT IN)
- › Audio Output (RECORDER, PHONES)
- › SR In/Out
- › AC Inlet

## SPECIFICATIONS

- › 70 W + 70 W (20 Hz-20 kHz, THD 0.1 %, 4 ohms)
- › 40 W + 40 W (20 Hz-20 kHz, THD 0.05 %, 8 ohms)
- › THD: 0.01 % (Rated Output -3 dB, 8 ohms, 1 kHz)
- › Guaranteed Speaker Impedance (2 Speaker Terminals): 4-16 ohms (A or B), 8-32 ohms (A+B), 4-16 ohms (Bi-Wiring)
- › Frequency Response: SACD/CD 5 Hz-100 kHz, 0 dB/-3 dB, PHONO (RIAA Equalization) MM 20 Hz-20 kHz,  $\pm 0.5$  dB
- › Signal-to-Noise Ratio (IHF, A Network, Short Circuited) SACD/CD: 105 dB, Phono: 77 dB (MM: 5 mV input), Power Amp Direct: 118 dB
- › Channel Separation SACD/CD: 90 dB (100 Hz), 90 dB (1 kHz), 75 dB (10 kHz) Power Amp Direct: 90 dB (100 Hz), 90 dB (1 kHz), 85 dB (10 kHz)
- › Power Requirements: AC 220-230 V, 50 Hz
- › Power Consumption: 175 W
- › Power Consumption During Standby: 0.3 W
- › Dimensions (W x H x D): 435 x 128 x 360 mm
- › Weight: 7.9 kg

## INTEGRATED TECHNOLOGIES



This logo is used for Pioneer products capable of 96 kHz/24-bit or above WAV/FLAC file playback, and Pioneer amplifiers, speakers, or headphones supporting over 40 kHz high-frequency reproduction, designed to derive maximum performance from Hi-Resolution Audio. This logo is a registered trademark of Japan Audio Society.