



PL-30-K

Audiophile Stereo Turntable with Double-Layered Chassis, Built-in Phono Equaliser, and User-Friendly Features



MAIN FEATURES

- > Full-Automatic Operation
- > Double-Layered Chassis with 4 mm-Thick Metal Plate and Low Centre of Gravity Provides Stable Playback
- > Built-in Phono Equaliser with On/Through Selector: On for Connecting Amps without Phono Terminal, Through When Using External Phono Equaliser
- > High-Performance MM Cartridge Included
- > Original 5 mm-Thick Rubber Mat Suppresses External Vibration While Firmly Gripping the Record
- > Aluminium Die-Cast Platter
- > Aluminium Die-Cast Tone Arm
- > Aluminium Die-Cast Exchangeable Headshell
- > Anti-Skating Dial for Accurate Tracking
- > Speed Selector
- > Size Selector
- > Gold-Plated Pin Plug
- > Detachable Power Cord
- > Unobtrusive Design Matches Any Décor

INCLUDED ACCESSORIES

- > Turntable
- > Turntable Sheet
- > Dust Cover with Removable Hinges
- > Adapter for EP Record
- > Balance Weight
- > Headshell with Cartridge
- > Spare Lead Wires
- > Power Cord
- > Operating Instructions

MAIN SPECIFICATIONS

- > Power Requirements: AC 220-240 V, 50/60 Hz
- > Power Consumption: 2 W
- > Output: RCA (Stereo Pin Plugs) x 1
- > Maximum Dimensions (W x H x D): 435 x 110 x 372.6 mm
- > Main Unit Weight: 5.6 kg

TURNTABLE SPECIFICATIONS

- > Drive Method: Belt Drive System
- > Wow and Flutter: 0.1% or Less WRMS (JIS WTD)
- > Motor: DC Servo Motor
- > S/N Ratio: 60 dB (DIN-B)
- > Rotation Speed: 33 1/3 rpm, 45 rpm

TONE ARM SPECIFICATIONS

- > Arm Type: Static Balance Straight Type Tone Arm
- > Effective Length: 221.5 mm
- > Overhang: 19 mm
- > Stylus Pressure Variable Range: 0 g to 4.0 g (1 scale 0.1 g)
- > Proper Cartridge Weight: 4.5 g to 9.5 g (Single Cartridge)
- > Cartridge Type: MM Type
- > Headshell Weight: 10.0 g (Including Screws and Nuts)