

**ROTEL**

STEREO INTEGRATED AMPLIFIER

A11



**AVAILABLE AT  
DIGITAL CINEMA**



2 x 50 Watts (8 Ohms)  
of classic Rotel Class  
AB power



Includes remote  
control



Moving magnet  
phono input for  
turntable connection



Bluetooth with  
aptX and AAC



Texas Instruments Digital  
to Analogue Converter

The A11 Integrated Amplifier is based on the successful 14 Series models. The output power utilizes classic Rotel Class AB amplification rated at 50 Watts per channel into 8 ohms. Source inputs include an MM Phono Stage for classic vinyl lovers, aptX and AAC Bluetooth for wireless audio streaming and an array of 4 RCA analog inputs for ultimate flexibility. The front panel graphic display and IR remote control ensure effortless and simplified control of your audio.

All of this is complimented by a Rotel in-house custom designed oversized toroidal transformer using steel and copper raw materials only from proven, trusted suppliers. The resulting acoustic performance speaks for itself under all loading conditions with even the most difficult speaker loads.

Rotel integrated  
amplifiers bring your  
sources to life with  
amazing fidelity.  
See more at

[rotel.com.au](http://rotel.com.au)



STEREO INTEGRATED AMPLIFIER

A11



SPECIFICATIONS

<b>Continuous Power Output</b> (20 - 20kHz, < 0.03%, 8 ohms)	50 watts/ch	<b>Tone Controls - Bass / Treble</b>	± 10 dB at 100Hz / 10kHz
<b>Total Harmonic Distortion</b> (20 Hz - 20 kHz at rated power)	< 0.03%	<b>Signal to Noise Ratio</b> ("A" weighting)	
<b>Intermodulation Distortion</b> (60 Hz : 7kHz, 4:1)	< 0.03%	Phono Input	85 dB
<b>Frequency Response</b>		Line Level Inputs	100 dB
Phono Input	20Hz - 20kHz, ± 0.5dB	<b>General</b>	
Line Level Inputs	10Hz - 100kHz, ± 0.5dB	<b>Power Requirements</b>	
<b>Damping Factor</b> (20 - 20,000 Hz, 8 ohms)	140	Europe	230V, 50Hz
<b>Input Sensitivity / Impedance</b>		USA	120V, 60Hz
Phono Input	2.3 mV / 47k Ohms	<b>Power Consumption</b>	160 watts
Line Level Inputs	180 mV / 47k Ohms	<b>Standby Power Consumption</b>	< 0.5 watts
<b>Input Overload</b>		<b>BTU</b> (4 ohms, 1/8 power)	479 BTU/h
Phono Input	50 mV	<b>Finishes</b>	Silver and Black
Line Level Inputs	4 V	<b>Dimensions</b> (W x H x D)	430 x 93 x 345mm 17" x 3 5/8" x 13 1/2"
<b>Preamp Output / Impedance</b>	1 V / 470 Ohms	<b>Front Panel Height</b>	80mm, 3 1/8"
		<b>Weight</b> (net)	6.85kg, 15.1 lb

Rotel integrated amplifiers bring your sources to life with amazing fidelity. See more at

[rotel.com.au](http://rotel.com.au)

