

## Technical Specifications



|                            |  |
|----------------------------|--|
| <b>Operation</b>           | semi-automatic   |
| <b>Drive System</b>        | internal flat drive belt   |
| <b>Motor</b>               | electronically controlled DC motor   |
| <b>Speeds</b>              | 33-1/3, 45 rpm   |
| <b>Speed Select</b>        | electronically   |
| <b>Platter</b>             | 12" / 0.6 kg (aluminium, non-magnetic)   |
| <b>Tonearm</b>             | THORENS® TP 19-1   |
| <b>Pick-up Cartridge</b>   | THORENS® TAS 267   |
| <b>Anti-skating (Bias)</b> | by spring (adjustable)   |
| <b>Automatic Shut-off</b>  | opto-electronically  |
| <b>Cable Capacitance</b>   | 160 pF   |
| <b>Power Supply</b>        | external mains adaptor (115-230 V / 50-60 Hz depending on type)                |
| <b>Dimensions</b>          | 420 x 130 x 365 mm (W x H x D)   |
| <b>Weight</b>              | 6.7 kg   |
| <b>Finish</b>              | solid wooden plinth with black structured enamel                               |
| <b>Scope of Delivery</b>   | mains adapter, dust cover (acrylic), RCA interconnects, operating instructions |
| <b>Optional</b>            | built-in phono preamplifier (TD 235 phono)                                     |